

NUMBER: B090R1133-0

DATE: AUG. 6, 1993

SUPERSEDES:

SERVICE BULLETIN

Effective Serial Number:

ALL UNITS WITH QUARTZ FLOODLIGHTS

Ride: ALL RIDES

Subject: FLOOD LIGHT SAFETY

Chance Rides, Inc. now installs a special tape to the lens of the factory installed quartz flood lights used on amusement rides. This tape helps prevent the glass lens from falling apart even if it should break. This provides an additional measure of safety to personnel and passengers of the rides.

Chance Rides, Inc. requires all owner/operators of Chance Rides products with quartz flood lights to order and install tape, part number 45001700 as outlined in this bulletin. Tape comes in 10 inch width and is available by the foot. Order the appropriate amount, to the nearest foot, to insure all flood lights have been completely covered. This tape is available at no charge if ordered within 90 days of the date on this bulletin.

All work must be performed by qualified personnel, capable of understanding the function of the parts and their proper installation.

NOTICE

Use only those components authorized, specified or provided by Chance Rides, Inc.

Chance Rides, Inc. SPECIFICALLY DISCLAIMS ANY LIABILITY for losses associated with any unauthorized alterations and/or modifications or additions and installations of unauthorized components.

Installation Instructions

- Remove glass lens from light fixture.
- 2. Measure and trim tape to fit lens.
- Carefully remove the backing from the tape.
- Apply tape to glass in such a manner as to prevent air bubbles from forming.


NOTE:

A fine mist of water applied to the glass first may help eliminate air bubbles as well as increase the ease by which the tape is applied.

IMPORTANT:

If water is used, make sure all water has evaporated from between the glass and the tape before turning light on. A period of at lease two days may be required for evaporation.

CAUTION: Quartz flood lights can get extremely hot. Do not attempt to apply tape after light has been on.



PAGE 2 OF 2 B090R1133-0